

Speed Queen



Multi-Housing

Stack Washer/Dryers

A whole new level of efficiency.

Commercial Dryer and Stack Specifications

	Single Dryer	Single Dryer	Stack Dryer	Stack Washer/Dryer
Available Controls	Quantum Gold	Quantum Gold, E-Mech	Quantum Gold, E-Mech	Quantum Gold
Available Control Location	Front	Rear	Front	Front
Capacity - lb (kg)	18 (8.2)	18 (8.2)	18 (8.2)	See front control front load washer and dryer specs to left
Cylinder Volume - cu. Ft. (liters)	7.0 (198)	7.0 (198)	7.0 (198)	
Width - in (mm)	26.875 (683)	26.875 (683)	26.875 (683)	
Depth - in (mm)	28 (711)	28 (711)	28 (711)	
Height - in (mm)	44.34 (1126)	43 (1092)	78.17 (1986)	78.17 (1986)
Spin Speed G-Force (RPM)	-	-	-	See front control front load washer and dryer specs to left
Motor Size - HP (kw)	0.33 (0.25)	0.33 (0.25)	0.33 (0.25)	
Water Consumption per Cycle - g (l)**	-	-	-	
IWF (Water Factor)**	-	-	-	
IMEF (Modified Energy Factor)**	-	-	-	
Available Heat Sources	Gas or Electric	Gas or Electric	Gas or Electric	
Available Heating Element (Electric W)	5350 @ 240V	5350 @ 240V	5350 @ 240V	
Gas Inlet Connection - in (mm)	3/8 (9.5)	3/8 (9.5)	3/8 (9.5)	
Gas Consumption - BTU/Hr	25,000	25,000	25,000	
Exhaust Outlet Dia. - in (mm)	4 (102)	4 (102)	4 (102)	
Exhaust Airflow - cfm (liters/sec)	220 (105)	220 (105)	220 (105)	See front control front load washer and dryer specs to left
Available Water Temperatures	-	-	-	
Available Cycles*	High, Medium, Low, Delicates, No Heat	High, Medium, Low, Delicates, No Heat	High, Medium, Low, Delicates, No Heat	
Water Pressure - PSI (Bar)	-	-	-	
Cycle Indicator Lights	Yes	Yes	Yes	See front control front load washer and dryer specs to left
Cylinder Finish	Galvanized	Galvanized	Galvanized	
Available Colors	White	White	White	
Door Type (Solid/Window)	Solid	Solid	Solid	
Available Electrical Requirements - (Voltage/Hz/Ph - Circuit Amperage)	Gas: 120/60/1 - 15 Amp, Electric: 208-240/60/1 - 30 Amp	Gas: 120/60/1 - 15 Amp, Electric: 208-240/60/1 - 30 Amp	Gas: 120/60/1 - 15 Amp, Electric: 208-240/60/1 - 30 Amp	See front control front load washer and dryer specs to left
Net Weight - lb (kg)	150 (68)	150 (68)	270 (122)	385 (175)
Shipping Weight - lb (kg)	161 (73)	161 (73)	280 (127)	417 (189)
Shipping Width - in (mm)	29.5 (749)	29.5 (749)	30 (762)	30 (762)
Shipping Depth - in (mm)	30.5 (775)	30.5 (775)	33 (838)	34 (864)
Shipping Height - in (mm)	45 (1143)	45 (1143)	80 (2032)	80 (2032)
Available Agency Approvals	Electric: cULus, Gas: cCSAus	Electric: cULus, Gas: cCSAus	Electric: cULus, Gas: cCSAus	Electric: cULus, Gas: cCSAus